Taita Chemical Company, Limited



Head Office: 12FL, No.39, Ji-Hu, Taipei, Taiwan

Tel: (886) 2-8751-6888 Fax: (886) 2-2659-9504 **Product Information**

Ver. : 3.0

台達通用級聚苯乙烯 TAITAREX GPPS/HIPS

(General Purpose Polystyrene) GPPS 861N/B

Characteristics

- Injection Grade
- The most state of the art form US NOVA CHEMICAL
- Low Residual Monomer
- Good Heat Resistance
- Mold Dimension Stability
- **Good Transparency**
- Easy Processing

Applications

- Electrical appliances
- house hard wares
- cassette & cosmetic cases
- lamp decoration
- toys.

Physical Properties

Properties	ASTM method	Test Condition	Unit	Typical Value
Specific Gravity	D542			1.046
Melt Flow Index	D1238	200°C → 5 kg load	g/10min	7.0
Tensile Strength at Yield	D638	23°C,1/8" Sample	kg/cm2	450
Elongation at Break	D638	23°C,1/8" Sample	%	2.0
Izod Impact Strength	D256	23°C,A method,notched 1/4"×1/2"×5/2"	kg-cm/cm	1.4
Vicat Softening Temperature	D1525	1 kg load [,] 3 mm Thick (120 °C/hr)	°℃	100
Flammability	UL-94	1/16" Sample	File No. E50263	94HB
Residual SM monomer			ppm	300
Haze		2.8mm thick	%	0.4

Note: The data listed represent average values and are believed to be reliable. They are given for information; no guarantee of their accuracy is made.